

## AGME RA RADIAL RIVETING MACHINES

MODEL	RA-6	RA-12	RA-14	RA-16	RA-18	RA-20
<b>Max. final diameter in 400 N/mm<sup>2</sup> steel</b>	6 mm	12 mm	14 mm	16 mm	18 mm	20 mm
<b>Adjustable riveting stroke</b>	5-40 mm	5-40 mm	5-50 mm	5-50 mm	5-50 mm	5-50 mm
<b>Max. air pressure</b>	6 bars	6 bars	6 bars	-	6 bars	-
<b>Max. hydraulic force</b>	-	-	-	40 bars	-	65 bars
<b>Axial force</b>	475 daN	1.265 daN	1.880 daN	2.500 daN	3.240 daN	4.000 daN
<b>Adjustable riveting time</b>	0-5 sec.	0-5 sec	0-5 sec	0-5 sec	0-5 sec	0-5 sec
<b>Power circuit</b>	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz	230 / 400V 50 / 60 Hz
<b>Installed power</b>	0,4 kW	0,7 kW	1,6 kW	2,8 kW	1,6 kW	2,8 kW
<b>Control circuit</b>	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC	24 V DC
<b>Two hand safety control</b>	Included	Included	Included	Included	Included	Included
<b>Operation control in 6 languages</b>	Included	Included	Included	Included	Included	Included
<b>Parts counters</b>	Included	Included	Included	Included	Included	Included
<b>Stroke centesimal adjustment</b>	Included	Included	Included	Included	Included	Included
<b>Weight</b>	155 Kg	160 Kg	285 KG	290 Kg	300 Kg	295 Kg

- The RA-4 and RA-30 riveting machines are built on customer's request

